

EXTENDED SPEED SLEEVE CFS-SL GA L

Product description

- Re-penetrable cable management device for electrical and telecom professionals

Product features

- Fast installation
- Easy penetration and re-penetration
- Industry's best "Air Movement" ratings
- Low L-ratings
- Withstands the rigors of usage and time
- Can be installed in wall and floor applications
- May be "ganged" together

Areas of application

- Cable and cable bundles

For use with


- Wall thicknesses from 8" up to 11¹³/₁₆"
- Concrete floors rated up to 3 hours
- Concrete/masonry block walls rated up to 4 hours
- Gypsum walls rated up to 4 hours

Examples

- Electrical wiring
- Premise wiring
- Low voltage and datacom

Installation instructions

- See Hilti literature or third-party listings for complete application and installation details



Technical data

4" (102 mm)

OD (device only)	4.3" (110 mm)
OD (flange)	6.7" (170 mm)
ID	3.6" (92 mm)
Total length	16.25" (413 mm)
Weight (device and flanges)	2.6 lbs
Temperature resistance	-22°F to 212°F (-6°C to 100°C)
Intumescent activation	Approx. 320°F (160°C)
Expansion ratio (unrestricted)	1:40
Metal	Steel with zinc coating
Plastic	ABS
Fabric	Glass-fiber
Tested in accordance with	UL 1479, ASTM E 814, CAN/ULC-S115