

# FIRESTOP PUTTY STICK CP 618

## Product description

- Easily moldable and reusable firestop putty designed to help create a fire and smoke barrier around cables and metal pipes

## Applications for use

- Non-hardening, firestop putty for single or bundled cables and non-combustible pipe penetrations
- Concrete-, masonry-, and gypsum-wall assemblies
- Wall and floor assemblies rated up to 3 hours
- Where telecommunication and data lines penetrate gypsum-wall assemblies
- Where steel conduit and EMT penetrate concrete- and block-wall assemblies
- Where blank openings exist in concrete- and block-wall assemblies

## Advantages

- Quicker, simpler to install and reusable — does not harden over time
- Approval for virtually any transit type — telecom, low- and medium-voltage cables, conduits, metal pipes, and blank openings
- Adheres to concrete-, masonry-, and gypsum-wall assemblies
- Mold and mildew resistant
- Acoustically tested according to ASTM E90
- Asbestos, formaldehyde and LABS free
- Red list compliant
- Living Building Challenge (LBC) compliant

## Installation instructions

- See Hilti literature or third-party listings for complete application and installation details



## Technical Data

<b>Chemical basis</b>	Moldable putty
<b>Color</b>	Red
<b>Recommended application temperature</b>	32° F to 104° F (0° C to 40° C)
<b>Storage and transportation temperature range</b>	23° F to 104°F (-5° C to 40° C)
<b>Temperature resistance range</b>	-4° F to 104°F (-20° C to 40° C)
<b>Mold and mildew performance</b>	Class 0 (ASTM G21-96)
<b>Tested in accordance with</b>	UL 1479, CAN / ULC-S115, ASTM E814
<b>Surface burning characteristics (ASTM E84)</b>	Flame Spread 15 Smoke Development 10
<b>Product activation</b>	284° F (140° C)
<b>LEED VOC</b>	12.18 g/L
<b>Can be painted</b>	No
<b>Acoustics performance</b>	49 (relates to specific construction) ASTM E90
<b>Shelf life</b>	Not relevant
<b>Volume per unit</b>	18 in <sup>3</sup>

Order designation	Sales pack quantity	Item number
CP 618 Putty stick (single)	1	3474775
CP 618 Putty stick	12	314721

