

FIRESTOP PLUG CFS-PL

Product description

- Reusable intumescent firestop solution for permanent or temporary cable openings in walls and floors

Applications for use

- Temporary or permanent sealing of cables — single or bundled cables
- Sealing single or multiple cables in small openings
- Sealing openings where re-penetration and retrofitting of cables is frequent
- Situations where ease and speed of installation are important

Advantages

- Fast and easy installation — no special tools required, helps reduce installation time
- Immediately functional after installation
- Economical to use with short installation times
- Easy installation — no special tools required
- Suitable for laying new cables later
- One sided wall systems available
- Halogen, asbestos and solvent free
- Versatile in use (temporary or permanent protection)
- Smoke resistant
- May be suitable for “clean room” installation
- Ideal for the temporary closing of empty core holes
- Sealant free, ready-to-use and reusable

Installation instructions

- See Hilti literature or third-party listings for complete application and installation details



Technical Data

| | |
|---|--|
| Chemical basis | Polyurethane Foam |
| Color | Red |
| Recommended application temperature | 40° to 104°F (5° to 40°C) |
| Storage and transportation temperature range | 32° to 140°F (0° to 60°C) |
| Temperature resistance range | 5° to 140°F (-15° to 60°C) |
| Density | 0.27 g/cm ³ |
| Mold and mildew performance | Class 0 (ASTM G21-96) |
| Tested in accordance with | UL 1479, CAN/ULC-S115, ASTM E814 |
| Surface burning characteristics (ASTM E84) | Flame Spread 10 Smoke Development 15 |
| Intumescent activation | 392°F (200°C) |
| LEED VOC | 4.9 g/L |
| Can be painted | Yes |
| Acoustics performance | 54 (relates to specific construction) ASTM E90 |
| Shelf life | Unlimited |
| Expansion ratio | 1:3 |

| Order designation | Sales pack quantity | Item number |
|-------------------------|---------------------|-------------|
| CFS-PL Plug 2" (single) | 1 | 3473763 |
| CFS-PL Plug 2" | 10 | 2030021 |
| CFS-PL Plug 4" (single) | 1 | 3473764 |
| CFS-PL Plug 4" | 6 | 2030022 |

| Dimensions (D x H) | Size |
|-------------------------|------------------|
| CFS-PL Firestop Plug 2" | 2" x 3" (5x8cm) |
| CFS-PL Firestop Plug 4" | 4" x 3" (10x8cm) |

