

HIT-RE 500-SD

Safety information for 2-Component-products

Date of issue: 27/09/2018

Revision date: 27/09/2018

Supersedes: 08/11/2017

Version: 9.2

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-RE 500-SD



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS-CA)

Skin corrosion/irritation, Category 1A	H314
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Label elements

GHS-CA labelling

Hazard pictograms (GHS-CA)



GHS05



GHS07



GHS08



GHS09

Signal word (GHS-CA)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS-CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H360 - May damage fertility..
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.


HIT-RE 500-SD

Safety information for 2-Component-products

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-component-foilpack, contains:
 Component A: Epoxy resin, Reactive diluent, inorganic filler
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification (GHS-CA)
HIT-RE 500-SD, A		1	pcs	Skin Corr. 1C, H314 Skin Sens. 1, H317 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
HIT-RE 500-SD, B		1	pcs	Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

SECTION 4: General advice

No data available

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters Avoid release to the environment Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Technical measures	Comply with applicable regulations
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Avoid contact during pregnancy/while nursing
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product On land, sweep or shovel into suitable containers Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

HIT-RE 500-SD

Safety information for 2-Component-products

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Drink plenty of water Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 09/27/2018

Revision date: 09/27/2018

Supersedes: 11/08/2017

Version: 8.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500-SD, B
Product code	BU Anchor

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906310 - F +49 8191 90176310
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Skin Corr. 1A	H314
Skin Sens. 1	H317
Aquatic Acute 3	H402
Aquatic Chronic 3	H412

Full text of H statements : see section 16

2.2. Label elements

GHS-CA labelling

Hazard pictograms (GHS-CA)



GHS05

GHS07

Signal word (GHS-CA)

Danger

Hazard statements (GHS-CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
m-Xylylenediamine		(CAS-No.) 1477-55-0	25 - 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Quartz (SiO ₂)		(CAS-No.) 14808-60-7	10 - 25	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Drink plenty of water. Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Corrosive vapours.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 oral	660 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.34 mg/l/4h

Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 11.5
Serious eye damage/irritation	Serious eye damage, category 1, implicit pH: 11.5
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-RE 500-SD, B	
Viscosity, kinematic	35460.993 mm ² /s

Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
-----------------	--

m-Xylylenediamine (1477-55-0)	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l

12.2. Persistence and degradability

HIT-RE 500-SD, B	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-RE 500-SD, B	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
14.1. UN number			
3259	3259	3259	3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ADR	IMDG	IATA	RID
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Orange plates	<div style="border: 2px solid black; padding: 5px; text-align: center; width: fit-content; margin: 0 auto;"> <div style="background-color: orange; color: black; font-weight: bold; padding: 2px 10px;">80</div> <div style="background-color: orange; color: black; font-weight: bold; padding: 2px 10px;">3259</div> </div>

Tunnel restriction code (ADR) E

- Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
Stowage and segregation (IMDG)	Separated from' acids.
MFAG-No	154

- Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

- Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08
Carriage prohibited (RID)	No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. National regulations

HIT-RE 500-SD, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

m-Xylylenediamine (1477-55-0)
Listed on the Canadian DSL (Domestic Substances List)
Quartz (SiO₂) (14808-60-7)
Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

m-Xylylenediamine (1477-55-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quartz (SiO₂) (14808-60-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Date of issue	09-27-2018
Revision date	09-27-2018
Supersedes	11-08-2017
Other information	None.

Full text of H-statements:

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H350	May cause cancer.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 09/27/2018

Revision date: 09/27/2018

Supersedes: 11/08/2017

Version: 9.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500-SD, A
Product code	BU Anchor

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906310 - F +49 8191 90176310
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Skin Corr. 1C	H314
Skin Sens. 1	H317
Repr. 1B	H360
Aquatic Acute 2	H401
Aquatic Chronic 2	H411
Full text of H statements : see section 16	

2.2. Label elements

GHS-CA labelling

Hazard pictograms (GHS-CA)



Signal word (GHS-CA)

Danger

Hazard statements (GHS-CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H360 - May damage fertility..
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Quartz (SiO ₂)		(CAS-No.) 14808-60-7	25 - 40	Carc. 1A, H350

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-bis(4-(2,3-epoxypropyloxy)phenyl)propane / 2,2-bis(4-glycidylloxyphenyl)propane / 2,2-bis(4-hydroxyphenyl)propane bis(2,3-epoxypropyl)ether / 2,2-bis(4-hydroxyphenyl)propane diglycidyl ether / 2,2-bis(para-(2,3-epoxypropoxy)phenyl)propane / 2,2-bis(para-(2,3-glycidylloxy)phenyl)propane / 2,2-bis(para-glycidylloxyphenyl)propane / 2,2-bis(para-hydroxyphenyl)propane, diglycidyl ether / 2,2-bis(p-glycidylloxyphenyl)propane / 2,2-bis(p-hydroxyphenyl)propane, diglycidyl ether / 2,2-bis[4-(2,3-epoxypropoxy)phenyl]propane / 2,2-bis-[4(2,3-epoxypropyloxyphenyl)]propane / 4,4'-bis(2,3-epoxypropoxy)diphenylmethane / 4,4'-dihydroxydiphenyldimethylmethane diglycidyl ether / 4,4'-isopropylidenebis(1-(2,3-epoxypropoxy)benzene) / 4,4'-isopropylidenediphenol diglycidyl ether / 4,4'-isopropylidenediphenol epichlorohydrin resin / araldite 6005 / BADGE / bis(4-glycidylloxyphenyl)dimethylmethane / bis(4-hydroxyphenyl)dimethylmethane diglycidyl ether / bis[4-(2,3-epoxypropoxy)phenyl]propane / bisphenol A diglycidyl ether / bisphenol A epichlorohydrin condensate / BPDGE / DER332 / dian diglycidyl ether / dian-bis(glycidyl ether) / diglycidyl bisphenol A / diglycidyl bisphenol A ether / diglycidyl diphenylolpropane ether / diglycidyl ether of 2,2-bis(4-hydroxyphenyl)propane / diglycidyl ether of 2,2-bis(para-hydroxyphenyl)propane / diglycidyl ether of 4,4'-isopropylidenediphenol / diglycidyl ether of bisphenol A / diomethane diglycidyl ether / epi-rez 508 / epi-rez 510 / epotuf 37-140 / epoxide A / ERL-2774 / GY 6010 / oligomer 340 / oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxy methylene)]bis- / p,p'-dihydroxydiphenyldimethylmethane diglycidyl ether / para,para'-dihydroxydiphenyldimethylmethane diglycidyl ether / propane, 2,2-bis(p-(2,3-epoxypropoxy)phenyl)-	(CAS-No.) 1675-54-3	25 - 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol		(CAS-No.) 9003-36-5	10 - 25	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Reaction products of hexane-1,6-diol with 2-(chloromethyl)		(CAS-No.) 933999-84-9	10 - 25	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
1,3 Propanediol, 2 ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane		(CAS-No.) 30499-70-8	5 - 10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 1B, H360

Full text of hazard classes and H-statements : see section 16

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Drink plenty of water. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

No additional information available

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	41 - 77 °F
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.
------------------------	--

8.2. Appropriate engineering controls

Environmental exposure controls	Avoid release to the environment.
---------------------------------	-----------------------------------

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment	Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.
-------------------------------	--



Hand protection	Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.
Eye protection	Wear security glasses which protect from splashes.
Skin and body protection	Wear suitable protective clothing.
Environmental exposure controls	Avoid release to the environment.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey.
Odour	characteristic.
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.46 g/ml DIN EN ISO 1183-3
Solubility	insoluble in water.
Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	43 Pa.s HN-0333
Explosive properties	Product is not explosive.
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Reaction products of hexane-1,6-diol with 2-(chloromethyl) (933999-84-9)	
LD50 oral rat	3010 mg/kg
LD50 dermal rat	> 2000 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/irritation	Serious eye damage, category 1, implicit

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility..
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-RE 500-SD, A	
Viscosity, kinematic	29452.055 mm ² /s

Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water Toxic to aquatic life with long lasting effects.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 fish 1	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
EC50 Daphnia 1	1.7 mg/l
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
ErC50 (algae)	> 11 mg/l (EPA 660/3 - 75/009, 72 h, Scenedesmus sp., Static system, Fresh water, Experimental value)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

Reaction products of hexane-1,6-diol with 2-(chloromethyl) (933999-84-9)	
LC50 fish 1	30 mg/l
LC50 other aquatic organisms 1	23.1 mg/l
EC50 Daphnia 1	47 mg/l
NOEC (acute)	18 mg/l

12.2. Persistence and degradability

HIT-RE 500-SD, A	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-RE 500-SD, A	
Bioaccumulative potential	Not established.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)
Log Pow	>= 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	58.7 - 58.9 mN/m (20 °C, EU Method A.5: Surface tension)
Log Koc	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Other information Avoid release to the environment.

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg)			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

- Overland transport

Special provisions (ADR) 375

- Transport by sea

No data available

- Air transport

Special provisions (IATA) A197

- Rail transport

Carriage prohibited (RID) No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. National regulations

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)

Listed on the Canadian DSL (Domestic Substances List)

HIT-RE 500-SD, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)
Listed on the Canadian DSL (Domestic Substances List)

Quartz (SiO₂) (14808-60-7)
Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Reaction products of hexane-1,6-diol with 2-(chloromethyl) (933999-84-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3 Propanediol, 2 ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane (30499-70-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Quartz (SiO₂) (14808-60-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor	None
Date of issue	09-27-2018
Revision date	09-27-2018
Supersedes	11-08-2017

Indication of changes:

Section	Changed item	Change	Comments
3	Composition/information on ingredients	Modified	

Other information None.

Full text of H-statements:

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product