GC 52

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 07/29/2024 Revision date: 07/29/2024 Supersedes: 07/21/2023 Version: 3.1

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Name	GC 52
Product code	BU Direct Fastening

1.2. Recommended use and restrictions on use

Recommended use	For professional use only, Propellant for direct fastening tools.

1.3. Supplier

Supplier
Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
Oakville, Ontario L6H 0J8
Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet
Hilti AG
Feldkircherstraße 100
Schaan, 9494
Liechtenstein
T +423 234 2111
product.compliance-direct.fastening@hilti.com

1.4. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable gases, Category 1	H220	Extremely flammable gas.
Gases under pressure : Compressed gas	H280	Contains gas under pressure; may explode if heated.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)

Signal word (GHS CA) Danger

Hazard statements (GHS CA)
H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (GHS CA)
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.

P381 - In case of leakage, eliminate all ignition sources.
P403 - Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
but-1-ene	but-1-ene	CAS-No.: 106-98-9	40 - 60	Not classified
propene	propene	CAS-No.: 115-07-1	25 - 40	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Propane	Propane	CAS-No.: 74-98-6	5 - 10	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Polyethylene glycol	Polyethylene glycol	CAS-No.: 25322-68-3	1 - 3	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact: Gently wash with plenty of soap and water.
First-aid measures after eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion: Immediately consult a doctor/medical service.
First-aid measures general: Take off immediately all contaminated clothing.

4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms: No additional information available. No harmful effects are to be expected if used properly. The contained ingredients can be harmful, but they are hermetically enclosed in the article and can not be released.
The dismantling of the article is prohibited.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment: Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media: Carbon dioxide. Water spray. Dry powder. Alcohol resistant foam.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Explosion hazard	Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	On burning: release of (highly) toxic gases/vapours. Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.
Precautionary measures fire	Fight fire remotely due to the risk of explosion.
Other information	EN 12942. EN 12941.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Evacuate area. Remove ignition sources.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	Do not flush with water.
Other information	For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Do not breathe vapours. Prevent the build-up of electrostatic charge.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	Flammable gas. Do not pierce or burn, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	Keep cool. Protect from sunlight. Keep in fireproof place. Store in dry protected location to prevent any moisture contact.
Incompatible materials	Heat sources. Direct sunlight. Sources of ignition.
Heat and ignition sources	Keep away from heat and direct sunlight. Keep away from ignition sources.
Storage temperature	5 – 25 °C
Information on mixed storage	Do not store with DX powder cartridges.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

but-1-ene (106-98-9)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	n-Butene
OEL TWA	250 ppm
Notations and remarks	TLV® Basis: Body weight eff
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	n-Butene
OEL TWA	250 ppm
Notations and remarks	TLV® Basis: Body weight eff
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	n-Butene
OEL TWA	250 ppm
Notations and remarks	TLV® Basis: Body weight eff
Regulatory reference	ACGIH 2024
Canada (Ontario) - Occupational Exposure Limits	
Local name	Butenes, All isomers
OEL TWAEV	250 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	n-Butene
OEL TWA	250 ppm
Notations and remarks	TLV® Basis: Body weight eff
Regulatory reference	ACGIH 2024

propene (115-07-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	860 mg/m³
	500 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Propylene
VEMP (OEL TWAEV)	500 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

propene (115-07-1)	
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	500 ppm
Notations and remarks	TLV® Basis: Asphyxia; URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	500 ppm
Notations and remarks	TLV® Basis: Asphyxia; URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	500 ppm
Notations and remarks	TLV® Basis: Asphyxia; URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propylene
OEL TWAEV	500 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propylene
OEL TWA	500 ppm
Notations and remarks	TLV® Basis: Asphyxia; URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Yukon) - Occupational Exposure Limits	
Local name	Propylene
Notations and remarks	Asphyxiant substance
Regulatory reference	Yukon Occupational Health Regulations O.I.C. 1986/164

Propane (74-98-6)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane

Propane (74-98-6)	
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Propane
VEMP (OEL TWAEV)	1800 mg/m³
	1000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	Simple asphyxiant; EX (Substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

Propane (74-98-6)	
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	Asphyxiant substance
Regulatory reference	Yukon Occupational Health Regulations O.I.C. 1986/164

8.2. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)	0,12	

Eye protection:

Chemical goggles or safety glasses. CSA Z94.3:20

Skin and body protection:

When using cartridge operated tools, sufficient ear protection must be worn.

Respiratory protection:

No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Gas
Appearance	No data available
Colour	Colourless
Odour	characteristic
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	-88.6 °C
Auto-ignition temperature	287 °C
Decomposition temperature	No data available
Flammability (solid, gas)	Extremely flammable aerosol.
Vapour pressure	8300 hPa
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	0.6 g/cm³ (DIN 51757)
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	No data available
Explosive limits	Lower explosion limit: 1.6 vol % Upper explosion limit: 11.1 vol %

9.2. Other information

Heat of combustion	> 30 kJ/g NFPA 30B, Aerosol Classification Level: 3
Gas group	Gases under pressure : Compressed gas

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Possibility of hazardous reactions	No additional information available
Conditions to avoid	Heat. Sparks. Open flame. Direct sunlight. Overheating.
Incompatible materials	No additional information available
Hazardous decomposition products	No additional information available
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	Not classified (Based on available data, the classification criteria are not met)

propene (115-07-1)	
LC50 Inhalation - Rat	> 688 mg/m³

Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 280000 ppm (literature)

Polyethylene glycol (25322-68-3)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)

Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met)

propene (115-07-1)	
IARC group	3 - Not classifiable

Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	Not applicable

GC 52	
Vaporizer	Container fitted with a sealed spray attachment

Potential adverse human health effects and symptoms	No additional information available. No harmful effects are to be expected if used properly. The contained ingredients can be harmful, but they are hermetically enclosed in the article and can not be released. The dismantling of the article is prohibited.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	Due to the consistency along with the low water solubility of the product a bioavailability is unlikely.
Hazardous to the aquatic environment, short–term (acute)	Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long–term (chronic)	Not classified (Based on available data, the classification criteria are not met)

but-1-ene (106-98-9)	
LC50 - Fish [1]	14.8 mg/l (72 h; Quantitative structure-activity relationship (QSAR); Oncorhynchus mykiss)
EC50 - Crustacea [1]	18.7 mg/l (48 h; Quantitative structure-activity relationship (QSAR); Daphnia sp.)
EC50 96h - Algae [1]	14.9 mg/l (Quantitative structure-activity relationship (QSAR); algae)

propene (115-07-1)	
LC50 - Fish [1]	43.3 mg/l (72 h; Oncorhynchus mykiss (Rainbow trout); Quantitative structure-activity relationship (QSAR))
EC50 - Crustacea [1]	28.2 mg/l (48 h; daphnia; Quantitative structure-activity relationship (QSAR))
EC50 96h - Algae [1]	12.1 mg/l (algae; Quantitative structure-activity relationship (QSAR))

Polyethylene glycol (25322-68-3)	
LC50 - Fish [1]	> 100 mg/l (96 h; Poecilia reticulata; (OECD 203 method))
EC50 - Crustacea [1]	> 100 mg/l (48 h; Daphnia magna; (OECD 202 method))
ErC50 algae	100 – 1000 mg/l (96 h)
NOEC chronic fish	13671.586 mg/l (28 d; Poecilia reticulata (Guppy)
NOEC chronic crustacea	17475.27 mg/l (21 d; Daphnia magna; (calculated value))

12.2. Persistence and degradability

propene (115-07-1)	
Persistence and degradability	Readily biodegradable in water.

Propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.

Polyethylene glycol (25322-68-3)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

propene (115-07-1)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Kow)	1.77 (20 °C)

Propane (74-98-6)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

Polyethylene glycol (25322-68-3)	
Bioaccumulative potential	not bioaccumulable.

12.4. Mobility in soil

propene (115-07-1)

12.5. Other adverse effects

Ozone	Not classified (Based on available data, the classification criteria are not met)
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	Disposal must be done according to official regulations.
Waste treatment methods	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	Container under pressure. Do not drill or burn even after use.

Additional information	Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3150	UN 3150	UN 3150	UN 3150
14.2. UN proper shipping name			
HYDROCARBON GAS REFILLS FOR SMALL DEVICES	HYDROCARBON GAS REFILLS FOR SMALL DEVICES	Hydrocarbon gas Refills for small devices	HYDROCARBON GAS REFILLS FOR SMALL DEVICES
Transport document description			
UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1, (D)	UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1	UN 3150 Hydrocarbon gas Refills for small devices, 2.1	UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	6F
Limited quantities (ADR)	0
Excepted quantities (ADR)	E0
Packing instructions (ADR)	P209
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Special provisions for carriage - Loading, unloading and handling (ADR)	CV9
Special provisions for carriage - Operation (ADR)	S2
Tunnel restriction code (ADR)	D

Transport by sea

Limited quantities (IMDG)	0
Excepted quantities (IMDG)	E0
Packing instructions (IMDG)	P003
EmS-No. (Fire)	F-D

EmS-No. (Spillage)	S-U
Stowage category (IMDG)	B
Stowage and handling (IMDG)	SW2
MFAG-No	115

Air transport

PCA Excepted quantities (IATA)	E0
PCA Limited quantities (IATA)	Forbidden
PCA limited quantity max net quantity (IATA)	Forbidden
PCA packing instructions (IATA)	201
PCA max net quantity (IATA)	1kg
CAO packing instructions (IATA)	201
CAO max net quantity (IATA)	15kg
Special provisions (IATA)	A802
ERG code (IATA)	10L

Rail transport

Classification code (RID)	6F
Limited quantities (RID)	0
Excepted quantities (RID)	E0
Packing instructions (RID)	P209
Mixed packing provisions (RID)	MP9
Transport category (RID)	2
Special provisions for carriage - Loading, unloading and handling (RID)	CW9
Colis express (express parcels) (RID)	CE2
Hazard identification number (RID)	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

GC 52	
Canada DSL NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

but-1-ene (106-98-9)
Listed on the Canadian DSL (Domestic Substances List)

propene (115-07-1)
Listed on the Canadian DSL (Domestic Substances List)

Propane (74-98-6)
Listed on the Canadian DSL (Domestic Substances List)

Polyethylene glycol (25322-68-3)
Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

SDS Major/Minor	None
Issue date	07-29-2024
Revision date	07-29-2024
Supersedes	07-21-2023

Indication of changes			
Section	**Changed item**	**Change**	**Comments**
1.3	Department issuing data specification sheet	Modified	E-mail address of competent person responsible for the SDS
9.2	Physical and chemical properties	Added	NFPA 30B

Data sources	European Chemicals Agency, http://echa.europa.eu/. manufacturer.
Training advice	Department issuing data specification sheet.
Other information	NFPA 30B.

Full text of H-statements:	
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
ED	Endocrine disrupting properties
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
NOEC	No-Observed Effect Concentration

Abbreviations and acronyms:	
OECD	Organisation for Economic Co-operation and Development
N.O.S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative
NOAEL	No-Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level

SDS CA HILTI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.