

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 11/13/2024

Revision date: 11/13/2024

Supersedes: 04/17/2023

Version: 22.2

### SECTION 1: Identification

#### 1.1. Product identifier

Product form	Mixture
Trade name	CFR 1
Product code	BU Fire Protection



#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

**Supplier**

Hilti (Canada) Corp.  
2201 Bristol Circle  
Suite 700  
CA L6H 0J8 Oakville, Ontario  
Canada  
T +1905 8139200  
1-800-363-4458 toll free, F +1 905 813 9009  
[ca-sales@hilti.com](mailto:ca-sales@hilti.com)

**Department issuing data specification sheet**

Hilti AG  
Feldkircherstraße 100  
FL 9494 Schaan  
Liechtenstein  
T +423 234 2111  
[product.compliance-fire.protection@hilti.com](mailto:product.compliance-fire.protection@hilti.com)

#### 1.4. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
------------------	--

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

**Classification (GHS CA)**

Flammable aerosols, Category 1	H222	Extremely flammable aerosol.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H-statements: see section 16

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 2.2. GHS Label elements, including precautionary statements

#### GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H222 - Extremely flammable aerosol.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS CA)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P280 - Wear eye protection, protective clothing, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Acetone	acetone; propan-2-one; propanone 2-propanon / 2-Propanone / acetone / acetone NF / acetone oil / AI3-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / methylketon / Product code: S1212, S1260, U8903 / propan-2-one / propanone / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	CAS-No.: 67-64-1	40 – 80	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Eye Irrit. 2A, H319 STOT SE 3, H336
isobutane	isobutane 1,1-dimethylethane / A 31 (hydrocarbon) / hydrocarbon propellant A-31 / isobutane / isobutane (FAO) / isomethylethylmethane / methylpropane / petroleum gas / Product code 002D0326 / propane, 2-methyl- / R600a / trimethylmethane	CAS-No.: 75-28-5	25 – 60	Flam. Gas 1, H220 Press. Gas (Comp.), H280

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
propane	propane A 108 / dimethyl methane / ethylmethyl / hydrocarbon propellant A-108 / liquefied petroleum gas (=propane) / LPG (=propane) / LP-gas (=propane) / normal-propane / n-propane / petroleumgas (=propane) / productcode 002D0315 / propane / propane in gaseous state / propane, liquefied / propane, pur / propyl dihydride / propyl hydride / pyrogas	CAS-No.: 74-98-6	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell.
First-aid measures general	Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	May cause drowsiness or dizziness.
Symptoms/effects after eye contact	Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Carbon dioxide. Carbon monoxide. Vapours may form explosive mixture with air.

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	Take up liquid spill into absorbent material.
Other information	Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	5 – 25 °C

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure good ventilation of the work station.
Environmental exposure controls	Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gloves. Protective clothing. Protective goggles.

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>Hand protection:</b>				
Wear suitable gloves tested to EN374. Suitable for short-term work or as a splash guard: Nitrile rubber gloves (> 0.2 mm). In case of permanent product contact:				
Type	Material	Permeation	Thickness (mm)	Penetration
Protective gloves	Butyl rubber	6 (> 480 minutes)	0,5mm	

<b>Eye protection:</b>		
Type	Field of application	Characteristics
Safety glasses		

<b>Skin and body protection:</b>	
Wear suitable protective clothing	

<b>Respiratory protection:</b>	
Ensure good ventilation of the work station. If the occupational exposure limit is exceeded: Wear appropriate mask. (e.g. gas filter type A1-P2 according to EN 14387)	

**Personal protective equipment symbol(s):**



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol.
Colour	Colourless
Odour	characteristic
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	Not applicable
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Extremely flammable aerosol.
Vapour pressure	2500 – 2900 hPa at 20 °C
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	0.74 – 0.76 g/cm³

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	No data available
Explosive properties	Pressurised container: May burst if heated.
Explosive limits	No data available

### 9.2. Other information

Heat of combustion	> 30 kJ/g NFPA 30B, Aerosol Classification Level: 3
--------------------	---

## SECTION 10: Stability and reactivity

Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
Conditions to avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	No additional information available
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	6667 mg/kg
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))

isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause drowsiness or dizziness.

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	Not classified
------------------------	----------------

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Aspiration hazard	Not classified
CFR 1	
Vaporizer	Aerosol
Symptoms/effects	May cause drowsiness or dizziness.
Symptoms/effects after eye contact	Eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

Acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	> 12700 mg/l
ErC50 algae	> 530 mg/l 96h, Pseudokirchneriella subcapitata
isobutane (75-28-5)	
EC50 96h - Algae [1]	8.57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
propane (74-98-6)	
EC50 96h - Algae [1]	12 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

#### 12.2. Persistence and degradability

Acetone (67-64-1)	
Not rapidly degradable	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
isobutane (75-28-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
propane (74-98-6)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.



# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 12.3. Bioaccumulative potential

Acetone (67-64-1)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
isobutane (75-28-5)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
propane (74-98-6)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)

### 12.4. Mobility in soil

Acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
isobutane (75-28-5)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
propane (74-98-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

### 12.5. Other adverse effects

Ozone Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information




In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN number			
Not applicable	1950	1950	1950

# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TDG	DOT	IMDG	IATA
14.2. Proper Shipping Name			
Not applicable	Aerosols	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)			
Not applicable	2.1	2.1	2.1
Not applicable			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

### 14.6. Special precautions for user

#### TDG

Not applicable

#### DOT

UN-No.(DOT) : UN1950  
 DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
 DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
 DOT Packaging Bulk (49 CFR 173.xxx) : None  
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
 DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
 DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959  
 Limited quantities (IMDG) : SP277  
 Packing instructions (IMDG) : P207, LP02  
 EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
 EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
 Stowage category (IMDG) : None  
 MFAG-No : 126

#### IATA

PCA packing instructions (IATA) : 203  
 PCA max net quantity (IATA) : 75kg  
 CAO packing instructions (IATA) : 203  
 Special provisions (IATA) : A145, A167, A802



# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

CFR 1	
Canada DSL NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: Other information

SDS Major/Minor	None
Issue date	11-13-2024
Revision date	11-13-2024
Supersedes	04-17-2023

Indication of changes			
Section	Changed item	Change	Comments
			general update
8	Personal protective equipment	Modified	

Full text of H-statements:	
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)



# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Abbreviations and acronyms:	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disrupting properties
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class
VOC	Volatile Organic Compounds
SDS	Safety Data Sheet
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
OEL	Occupational Exposure Limit
OECD	Organisation for Economic Co-operation and Development
COD	Chemical oxygen demand (COD)
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
TLM	Median Tolerance Limit
STP	Sewage treatment plant

SDS\_CA\_Hilti



# CFR 1

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.